



HUSQVARNA 420EL

Electric-powered 2000W chainsaw with 16" bar for private use, or by non-garden professionals such as carpenters and electricians. Offers supreme overall performance, manoeuvrability and ergonomics, thanks to excellent cutting performance, robust design and slim body. Instant starting, high chain speed, 5 metre cord, comfortable soft-grip 90° front handle and convenient tool-less chain tensioning make it ideal for homeowners, indoor use and craftspeople.



Window for oil level

Transparent window makes it easy to check chain oil level.




Tool-less chain tensioning

Quick and easy chain tensioning and assembling of the bar and the chain without using any tools.

Easy to handle

The engine is positioned lengthwise for a slim, easy-to-handle saw.



Ergonomic handle

Ergonomically shaped handle for greater comfort and easy access to the controls.



FEATURES

- Easy to handle with slim saw body
- Tool-less chain tensioner
- Transparent chain oil level window
- Ergonomic handle with easy access to the controls.
- Fast, smooth cutting
- Increased safety, inertia activated chain brake

| Technical Specifications | |
|---|-------------------------|
| BATTERY | |
| Voltage | 230 V |
| CAPACITY | |
| Chain speed at max power | 14.5 m/s |
| Power rating | 2000 W |
| DIMENSIONS | |
| Article gross weight | 8100 g |
| Article net weight | 6850 g |
| Bar length (inch) | 16" |
| Bar length | 400 mm |
| Cable length | 0.45 m |
| Weight (excl. cutting equipment) | 4.7 kg |
| ENGINE | |
| Motor type | PMDC (2 brushed) |
| EQUIPMENT | |
| Chain type | H37 |
| Chainsaw sub-group | Part time use chainsaws |
| Gauge | 1.3 mm |
| Pitch | 3/8" |
| Source system | PAID |
| Sprocket type | Spur 6 |
| LUBRICANT | |
| Oil pump type | Automatic, gear driven |
| Oil tank volume | 0.18 l |
| Power/fuel type | Corded |
| MATERIALS | |
| Master pack: Paper + Cardboard | 0 g |
| Metal total | 50 g |
| Paper | 2800 g |
| Paper + Cardboard total | 2800 g |
| PE total | 0 g |
| PET total | 0 g |
| Plastic foil | 0 g |
| Plastic rigid | 600 g |
| Plastic total | 600 g |
| PS/EPS/HIPS total | 0 g |
| PACKAGING | |
| Packaging height | 265 mm |
| Packaging length | 613 mm |
| Packaging volume | 40.94 dm ³ |
| Packaging width | 252 mm |
| Quantity in Master pack | 1 |
| SOUND AND NOISE | |
| Sound power level, guaranteed (LWA) | 103 dB(A) |
| Sound power level, measured | 102 dB(A) |
| Sound pressure level at operators ear | 90.8 dB(A) |
| VIBRATION | |
| Equivalent vibration level,(ahv, eq), front handle, collapsed | 5.2 m/s ² |
| Equivalent vibration level,(ahv, eq), rear handle, extended | 3.9 m/s ² |

ACCESSORIES