




## Husqvarna 525P5S

Designed for professionals, the Husqvarna 525P5S pole saw with detachable shaft gives you longer reach and easy transporting between work sites. Low weight, excellent ergonomics and superior balance help you work comfortably even with less accessible vegetation. Easy to manoeuvre, its X-Torq® engine ensures rapid acceleration and high torque with low emissions and low fuel consumption.



### Detachable shaft

Detachable shaft for easy transport and storage.




### Intuitive controls

The choke and purge are easy to reach and understand.

### Auto return stop switch

Stop switch automatically resets to the ON position for trouble-free starting.



### Rear impact guard

The rear-impact guard protects the engine from wear and damage.



## FEATURES

- Auto return stop switch for easy starting
- Intuitive controls
- Detachable shaft easy transport and storage
- Rear impact guard
- Magnesium clutch housing ensures long service life
- Adjustable, automatic chain lubrication
- Air purge for easier cold starting
- Tool less chain tensioner
- Inertia balancing wheel reduces vibration
- Efficient air filter
- Easy to service and maintain starter
- Skid plate for engine protection
- X-Torq® engine cuts emission and fuel consumption

### Technical Specifications

<b>CAPACITY</b>	
Clutch engagement speed ( $\pm 120$ )	3850 rpm
Clutch engagement upper limit	5800 rpm
Idling speed	3000 rpm
Idling upper limit	3800 rpm
Maximum power speed	8500 rpm
Racing speed lower limit	11200 rpm
<b>DIMENSIONS</b>	
Article gross weight	10032 g
Article net weight	7350 g
Length, extended, including cutting equipment	340 cm
Size	12"
Tube diameter	24 mm
Tube length	2750 mm
Weight (excl. cutting equipment)	6.4 kg
<b>ENGINE</b>	
Cylinder bore	34 mm
Cylinder displacement	25.4 cm <sup>3</sup>
Cylinder stroke	28 mm
<b>EQUIPMENT</b>	
Chain type	H37
Gear ratio	1.06
Gear ratio	1
Pitch	3/8" mini
Source system	PAID
<b>LUBRICANT</b>	
Fuel consumption	395 g/kWh
Fuel consumption	0.395 kg/h
Fuel tank volume	0.51 l
Oil tank volume	0.2 l
Power/fuel type	Gasoline
<b>MATERIALS</b>	
Master pack: Paper + Cardboard	0 g
Metal total	0 g
Paper	49 g
Paper + Cardboard total	49 g
PE total	0 g
PET total	0 g
Plastic foil	0 g
Plastic rigid	23 g
Plastic total	23 g
PS/EPS/HIPS total	0 g
<b>PACKAGING</b>	
Packaging height	280 mm
Packaging length	2460 mm
Packaging volume	20.66 dm <sup>3</sup>
Packaging width	30 mm
Quantity in Master pack	1
<b>SOUND AND NOISE</b>	
Sound power level, guaranteed (LWA)	107 dB(A)
Sound power level, measured	107 dB(A)
Sound pressure level at operators ear	90 dB(A)
<b>VIBRATION</b>	
Daily Vibration (Aeqv)	3.7 m/s <sup>2</sup>
Daily Vibration Exposure (A8)	0.9 m/s <sup>2</sup>
Daily Vibration Time (Time factor)	0.5 h
Equivalent vibration level (ahv, eq) front handle	2.3 m/s <sup>2</sup>
Equivalent vibration level (ahv, eq) rear handle	3.7 m/s <sup>2</sup>

