




Husqvarna 525PT5S

Designed for professionals, the Husqvarna 525PT5S pole saw with telescopic shaft offers our longest reach, with excellent ergonomics and superior balance to help you achieve high-end results with minimum effort. Easy to manoeuvre, its X-Torq® engine ensures rapid acceleration and high torque with low emissions and low fuel consumption.



Telescopic tube

The tube has a telescopic function for quick cutting height adjustment




Intuitive controls

The choke and purge are easy to reach and understand.

Auto return stop switch

Stop switch automatically resets to the ON position for trouble-free starting.



Magnesium clutch housing

Robust magnesium clutch housing for tough professional use, ensuring a long service life.



FEATURES

- Auto return stop switch for easy starting
- Intuitive controls
- Telescopic tube for quick cutting height adjustment
- Magnesium clutch housing ensures long service life
- Rear impact guard
- Adjustable, automatic chain lubrication
- Air purge for easier cold starting
- Efficient air filter
- Easy to service and maintain starter
- Skid plate for engine protection
- X-Torq® engine cuts emission and fuel consumption

Technical Specifications

| CAPACITY | |
|---|--------------------------------------|
| Clutch engagement speed (± 120) | 3850 rpm |
| Clutch engagement upper limit | 5800 rpm |
| Idling speed | 3000 rpm |
| Idling upper limit | 3800 rpm |
| Maximum power speed | 8500 rpm |
| Racing speed lower limit | 11200 rpm |
| DIMENSIONS | |
| Article gross weight | 10148 g |
| Article net weight | 6400 g |
| Length, extended, including cutting equipment | 402 cm |
| Size | 10" |
| Tube diameter | 38 mm |
| Tube length | 3350 mm |
| Weight (excl. cutting equipment) | 7 kg |
| ENGINE | |
| Cylinder bore | 34 mm |
| Cylinder displacement | 25.4 cm ³ |
| Cylinder stroke | 28 mm |
| EQUIPMENT | |
| Chain type | H00 |
| Gear ratio | 1.06 |
| Gear ratio | 1 |
| Pitch | 1/4" |
| Source system | PAID |
| LUBRICANT | |
| Fuel consumption | 395 g/kWh |
| Fuel consumption | 0.395 kg/h |
| Fuel tank volume | 0.51 l |
| Lubricant type | Husqvarna 2 stroke or equiv. at 50:1 |
| Oil tank volume | 0.14 l |
| Power/fuel type | Gasoline |
| MATERIALS | |
| Master pack: Paper + Cardboard | 0 g |
| Metal total | 20 g |
| Paper + Cardboard total | 15700 g |
| PE total | 500 g |
| PET total | 0 g |
| Plastic foil | 500 g |
| Plastic rigid | 0 g |
| Plastic total | 500 g |
| PS/EPS/HIPS total | 0 g |
| PACKAGING | |
| Packaging height | 280 mm |
| Packaging length | 2460 mm |
| Packaging volume | 206.64 dm ³ |
| Packaging width | 300 mm |
| Pallet layers | 4 |
| Quantity in Master pack | 1 |
| SOUND AND NOISE | |
| Sound power level, guaranteed (LWA) | 107 dB(A) |
| Sound power level, measured | 107 dB(A) |
| Sound pressure level at operators ear | 89 dB(A) |
| VIBRATION | |
| Daily Vibration (Aeqv) | 6.7 m/s ² |
| Daily Vibration Exposure (A8) | 1.68 m/s ² |
| Daily Vibration Time (Time factor) | 0.5 h |
| Equivalent vibration level,(ahv, eq), front handle, collapsed | 6.3 m/s ² |
| Equivalent vibration level,(ahv, eq), front handle, extended | 4.1 m/s ² |
| Equivalent vibration level,(ahv, eq), rear handle, collapsed | 5.3 m/s ² |
| Equivalent vibration level,(ahv, eq), rear handle, extended | 6.7 m/s ² |