



HUSQVARNA TR 348

The TR 348 is a light-weighted, compact and easy to use tiller with great manoeuvrability. Equipped with high-quality transmission and Heli coiled tines and 48 cm working width it offers both great performance and durability.



Foldable handlebar

For easy storage and transport.



Drag bar

Easy-adjust drag bar, for balance in different working conditions.

Adjustable handlebar

Adjustable handlebar, both horizontally and vertically, for best working position.



Handlebar-mounted gear selection

Ergonomic handle with easy-access controls.



FEATURES

- Adjustable handlebar, both horizontally and vertically, for best working position.
- Drag bar for balanced operation
- Foldable handlebar for easy storage
- Ergonomic handle with easy-access controls
- Tine shield for minimized debris spray
- Reverse gear for optimum maneuverability

Technical Specifications	
CAPACITY	
Net power at preset rpm	3300 rpm
Net power at preset rpm Energy	4.5 kW
Power output	4.5 kW
Rotational speed (min/max) max	207 rpm
Rotational speed (min/max) min	103 rpm
Rotational speed	3300 rpm
DIMENSIONS	
Article gross weight	74000 g
Article net weight	71000 g
Tine diameter	300 mm
Tyre size	345 mm
Weight	73 kg
Working depth	15 cm
Working width	48 cm
ENGINE	
Cylinder displacement	208 cm ³
Engine brand	Briggs and Stratton
Engine name	950 Series
Fuel tank volume	3.6 l
Fuel tank volume	0.95 gal (US)
Motor/engine manufacturer	Briggs & Stratton
Transmission steps forward	2
Transmission steps reverse	1
Transmission type	Chain/Gear
Transport wheel/s	Not available
EQUIPMENT	
Chevron tyres	No
Cultivator type	Rear-tine
Drag bar	Yes
Foldable handlebar	Yes
Handlebar-mounted gear selection	No
Horizontally adjustable handlebar	Yes
Plant guards	No
Reverse gearbox	Yes
Rubber wheels	Included
Transport wheel/s	Not available
Vertically adjustable handlebar	Yes
LUBRICANTS	
Fuel consumption	505 g/kWh
Fuel tank volume	3.6 l
Power/fuel type	Petrol
MATERIALS	
Master pack: Paper + Cardboard	0 g
Metal total	0 g
Paper + Cardboard total	0 g
PE total	0 g
PET total	0 g
Plastic foil	0 g
Plastic rigid	0 g
Plastic total	0 g
PS/EPS/HIPS total	0 g
PACKAGING	
Packaging height	790 mm
Packaging length	1150 mm
Packaging width	600 mm
Quantity in Master pack	1
SOUND AND NOISE	
Sound power level, guaranteed (LWA)	98 dB(A)
Sound power level, measured	95.3 dB(A)
Sound pressure level at operators ear	84.5 dB(A)