



HUSQVARNA 372 XP®

A true professional saw in the larger mid-size class, built for very demanding applications. The crankcase and crankshaft are extra heavy-duty and the carburettor has vibration damping in order to handle high speeds and high loads. The saw combines low weight, high power and rapid acceleration with flexible operation. The XP® G model has both heated handles and carburettor.

Quick-release air filter

Facilitates cleaning and replacement of the air filter.



Adjustable oil pump

Adjustable oil pump makes it easy to set the chain lubrication according to your needs.

Air Injection®

Centrifugal air cleaning system for reduced wear and longer operating time between filter cleanings.



Side-mounted chain tensioner

Side-mounted chain tensioner makes chain adjustment quick and easy.



FEATURES

- Less filter cleanings with Air Injection
- Adjustable chain oil pump
- Quick-release air filter
- Quick and easy chain adjustment
- Magnesium crankcase designed for professional use
- Easy to maintain with snap locked filter cover
- Maximum durability for tough applications
- LowVib® sparing the user's arms and hands
- Smart Start® for easy starting
- Ergonomic grip with angled front handle
- Increased safety, inertia activated chain brake

Technical Specifications

CAPACITY

Chain speed at 133% of maximum engine power speed	28.5 m/s
Clutch engagement speed (±120)	3600 rpm
Clutch engagement upper limit	6000 rpm
Idling speed	2700 rpm
Idling upper limit	3500 rpm
Ignition module air gap	0.3 mm
Maximum power speed	9600 rpm
Power output	3.9 kW
Racing speed lower limit	12000 rpm
Torque, max.	4.3 Nm
Torque, max. at rpm	6600 rpm

CERTIFICATIONS

Cert machine dir. 2006/42/EC Decl. No.	0404/09/2089
Recyclability, today	80 %
Recyclable of weight of FE, Al and Mg	45 %

DIMENSIONS

Article gross weight	9508 g
Article net weight	8470 g
Bar length (inch)	24"
Weight (excl. cutting equipment)	6.3 kg

ENGINE

Carburetor	Walbro
Cylinder bore	50 mm
Cylinder displacement	70.7 cm ³
Cylinder stroke	36 mm
Electrode gap	0.5 mm
Ignition module air gap	0.3 mm
Max engine/motor RPM	13500 rpm
Spark plug	Champion RCJ7Y, NGK BPMR7A

EQUIPMENT

Bar mount type	Large
Chain type	H42
Chainsaw sub-group	Full time professional use chainsaws
Gauge	1.5 mm
Handle type	Standard
Pitch	3/8"
Source system	PAID
Sprocket type	Rim 7

LUBRICANT

Fuel consumption	480 g/kWh
Fuel consumption	1.9 kg/h
Fuel tank volume	0.77 l
Fuel type, min (Europe)	RON min 91 or alkylate
Lubricant type	Husqvarna or equiv. at 50:1
Oil pump capacity Max	21 ml/min
Oil pump capacity Min	4 ml/min
Oil pump type	Automatic
Oil tank volume	0.42 l
Power/fuel type	Gasoline

MATERIALS

Master pack: Paper + Cardboard	0 g
Metal total	0 g
Paper + Cardboard total	0 g
PE total	0 g
PET total	0 g
Plastic foil	0 g
Plastic rigid	0 g
Plastic total	0 g
PS/EPS/HIPS total	0 g

PACKAGING

Packaging height	250 mm
Packaging length	470 mm
Packaging volume	39.95 dm ³
Packaging width	340 mm

Technical Specifications

Quantity in Master pack	1
EMISSION DATA EPA	
Exhaust emissions (CO average)	348.5 g/kWh
Exhaust emissions (CO average)	752.5 g/kWh
Exhaust emissions (HC average)	126 g/kWh
Exhaust emissions (NOx average)	2.3 g/kWh
SOUND AND NOISE	
Sound level	103 dB(A)
Sound power level, guaranteed (LWA)	115 dB(A)
Sound power level, measured	114 dB(A)
Sound pressure level at operators ear	103 dB(A)
VIBRATION	
Daily Vibration (Aeqv)	8.0 m/s ²
Daily Vibration Exposure (A8)	5.4 m/s ²
Daily Vibration Time (Time factor)	3.7 h
Equivalent vibration level (ahv, eq) front handle	5.7 m/s ²
Equivalent vibration level (ahv, eq) rear handle	8.0 m/s ²